



d mm	Principal Dimension				Basic Load Rating		Fatigue Load Limit Pu kN	Speed Rating		Mass kg	Designation
	D	T	B	C	Dynamic C kN	Static Co		Reference Speed Grease RPM	Limiting Speed Oil		
110	150	25	25	20	125	224	24	3000	4300	1,25	32922
	170	38	38	29	233	390	42,5	2600	3600	3,05	32022X
	170	47	47	37	281	500	53	2600	3600	3,85	33022
	180	56	56	43	369	630	67	2600	3400	5,55	33122
	200	41	38	32	308	405	45	2400	3200	5,10	30222
	200	56	53	46	402	570	61	2400	3200	7,10	32222
	240	54,5	50	42	473	585	62	2200	2800	11,0	30322
	240	63	57	38	457	585	62	1900	2800	12,0	31322X
240	84,5	80	65	627	830	86,5	1900	2800	17,0	32322	
120	165	29	29	23	165	305	32	2600	3800	1,60	32924
	170	27	25	19,5	157	250	26,5	2600	3800	1,70	T4CB 120
	180	38	38	29	242	415	44	2400	3400	3,25	32024X
	180	48	48	38	292	540	56	2600	3400	4,20	33024
	215	43,5	40	34	341	465	49	2200	3000	6,15	30224
	215	61,5	58	50	468	695	72	2200	3000	9,15	32224
	260	59,5	55	46	561	710	73,5	2000	2600	1,40	30324
	260	68	62	42	539	695	73,5	1700	2400	1,55	31324
260	90,5	86	69	792	1120	110	1800	2600	2,15	32324	
130	180	32	32	25	198	365	38	2400	3600	2,40	32926
	200	45	45	34	314	540	55	2200	3000	4,95	32026X
	230	43,75	40	34	369	490	53	2000	2800	7,60	30226
	230	67,75	64	54	550	830	85	2000	2800	1,15	32226
	280	63,75	58	49	627	800	83	1800	2400	1,70	30326
	280	72	66	44	605	780	81,5	1600	2400	1,85	31326X
140	190	32	32	25	205	390	40	2200	3400	2,55	32928
	195	29	27	21	194	325	33,5	2200	3200	2,40	T4CB 140
	210	45	45	34	330	585	58,5	2200	2800	5,25	32028X
	250	45,75	42	36	418	570	58,5	1900	2600	8,65	30228
	250	71,75	68	58	644	1000	100	1900	2600	1,45	32228
	300	77	70	47	693	900	88	1500	2200	2,45	31328X
150	225	48	48	36	369	655	65,5	2000	2600	6,35	32030X
	225	59	59	46	457	865	86,5	2000	2600	8,15	33030
	270	49	45	38	429	560	57	1800	2400	1,10	30230
	270	77	73	60	737	1140	112	1700	2400	17,5	32230
	320	82	75	50	781	1020	100	1400	2000	29,5	31330X
160	240	51	51	38	429	780	78	1800	2400	7,75	32032X
	290	52	48	40	528	735	72	1600	2200	1,30	30232
	290	84	80	67	880	1400	132	1600	2200	2,55	32232
	340	75	68	58	913	1180	114	1500	2000	2,90	30332
170	230	32	30	23	251	440	43	1900	2800	3,45	T4DB 170
	230	38	38	30	286	585	55	1900	2800	4,50	32934
	260	57	57	43	512	915	90	1700	2200	10,5	32034X
	310	57	52	43	616	865	83	1500	2000	19,0	30234
	310	91	86	71	1010	1630	150	1500	2000	28,5	32234