



d mm	Principal Dimension				Basic Load Rating		Fatigue	Speed Rating		Mass	Designation
	D	T	B	C	Dynamic	Static	Load Limit Pu	Reference Speed Grease	Limiting Speed Oil		
	mm	mm	mm	mm	kN	kN	kN	RPM	kg		
85	130	29	29	22	140	224	25,5	3400	4800	1,35	32017
	130	36	36	29,5	183	310	34,5	3600	4800	1,75	33017
	140	41	41	32	220	340	38	3400	4500	2,45	33117
	150	30,5	28	24	176	220	25,5	3200	4300	2,05	30217
	150	38,5	36	30	212	285	33,5	3200	4300	2,60	32217
	150	49	49	37	286	430	48	3000	4300	3,70	33217
	180	44,5	41	34	303	365	40,5	2800	4000	4,85	30317
	180	44,5	41	28	242	285	33,5	2600	3800	4,60	31317
180	63,5	60	49	402	530	60	2800	4000	6,85	32317	
90	140	32	32	24	168	270	31	3200	4300	1,75	32018
	140	39	39	32,5	216	355	39	3200	4500	2,20	33018
	145	35	34	27	201	305	35,5	3200	4800	2,10	JM 718149 A/110
	150	45	45	35	251	390	43	3000	4300	3,10	33118
	150	45	45	35	251	390	43	3000	4300	3,10	33118
	160	32,5	30	26	194	245	28,5	3000	4000	2,55	30218
	160	42,5	40	34	251	340	38	3000	4000	3,35	32218
	190	46,5	43	36	330	400	44	2600	4000	5,65	30318
	190	46,5	43	30	264	315	36,5	2400	3400	5,90	31318
190	67,5	64	53	457	610	67	2600	4000	8,40	32318	
95	145	32	32	24	168	270	30,5	3200	4300	1,80	32019
	145	39	39	32,5	220	375	40,5	3200	4300	2,30	33019
	170	34,5	32	27	216	275	31,5	2800	3800	3,00	30219
	170	45,5	43	37	281	390	43	2800	3800	4,05	32219
	170	58	58	44	374	560	62	2600	3800	5,50	33219
	200	49,5	45	38	330	390	42,5	2600	3400	6,70	30319
	200	49,5	45	32	292	355	39	2400	3400	6,95	31319
	200	71,5	67	55	501	670	72	2400	3400	1,10	32319
	100	140	25	25	20	119	204	22,4	3200	4800	1,15
145		24	22,5	17,5	125	190	20,8	3200	4500	1,15	T4CB 100
150		32	32	24	172	280	31	3000	4000	1,90	32020X
150		39	39	32,5	224	390	41,5	3000	4000	2,40	33020X
157		42	42	34	246	400	42,5	3000	4300	2,90	HM 220149/110
165		47	46	39	314	480	53	2800	4300	3,90	JHM720249/210
165		47	46	39	314	480	53	2800	4300	3,90	T2EE 100
180		37	34	29	246	320	36	2800	3600	3,65	30220
180		49	46	39	319	440	48	2600	3600	4,90	32220
180		63	63	48	429	655	71	2400	3600	6,95	33220
215		51,5	47	39	402	490	53	2400	3200	8,05	30320
215		56,5	51	35	430	465	51	2400	3000	8,60	31320
215	77,5	73	60	572	780	83	2200	3000	1,25	32320	
105	160	35	35	26	201	335	37,5	2800	3800	2,40	32021X
	160	43	43	34	246	430	45,5	2800	3800	3,05	33021
	190	39	36	30	270	355	40	2600	3400	4,25	30221
	190	53	50	43	358	510	55	2600	3400	6,00	32221
	225	81,5	77	63	605	815	85	2000	3000	14,5	32321