



Principal Dimensions			load ratings		Speed Rating		Mass	Designation
d	D	B	dynamic C	Static C <sub>0</sub>	Grease	Oil	kg	-
mm				kN		RPM		
<b>50</b>	110	27	41.5	14.3	5600	6700	1.29	<b>1310</b>
	110	27	41.5	14.3	5600	6700	1.29	<b>1310K</b>
	110	40	64	20	5300	6300	1.78	<b>2310</b>
	110	40	64	20	5300	6300	1.78	<b>2310K</b>
	110	40	41.5	14.3	4300	--	1.78	<b>2310.2RS</b>
	90	20	22.8	8.15	7000	8500	0.53	<b>1210</b>
	90	20	22.8	8.15	7000	8500	0.53	<b>1210K</b>
	90	23	28	9.5	6700	8000	0.6	<b>2210</b>
	90	23	28	9.5	6700	8000	0.6	<b>2210K</b>
	90	23	22.8	8.15	5300	--	0.6	<b>2210K2RS</b>
90	23	22.8	8.15	5300	--	0.6	<b>2210.2RS</b>	
<b>55</b>	100	21	27	10	6300	7500	0.69	<b>1211</b>
	100	21	27	10	6300	7500	0.69	<b>1211K</b>
	100	25	39	12.5	5500	6600	0.75	<b>2211</b>
	100	25	39	12.5	5500	6600	0.75	<b>2211K</b>
	100	25	27	10	4800	--	0.8	<b>2211K.2RS</b>
	100	25	27	10	4800	--	0.8	<b>2211.2RS</b>
	120	29	51	18	5000	6000	1.6	<b>1311</b>
	120	29	51	18	5000	6000	1.6	<b>1311K</b>
	120	43	75	23.6	4800	5600	2.3	<b>2311</b>
	120	43	75	23.6	4800	5600	2.3	<b>2311K</b>
<b>60</b>	110	22	30	11.6	5600	6700	0.9	<b>1212</b>
	110	22	30	11.6	5600	6700	0.9	<b>1212K</b>
	110	28	45	16.5	5200	6200	1.1	<b>2212</b>
	110	28	45	16.5	5200	6200	1.1	<b>2212K</b>
	110	28	30	11.6	3800	--	1.1	<b>2212K.2RS</b>
	110	28	30	11.6	3800	--	1.1	<b>2212.2RS</b>
	130	31	57	20.8	4500	5300	2.0	<b>1312</b>
	130	31	57	20.8	4500	5300	2.0	<b>1312K</b>
	130	46	86.5	28	4300	5000	2.9	<b>2312</b>
	130	46	86.5	28	4300	5000	2.9	<b>2312K</b>
<b>65</b>	120	23	31	12.5	5300	6300	1.2	<b>1213</b>
	120	23	31	12.5	5300	6300	1.2	<b>1213K</b>
	120	31	57	19.5	4500	5200	1.4	<b>2213</b>
	120	31	57	19.5	4500	5200	1.4	<b>2213K</b>
	140	33	62	22.8	4300	5000	2.5	<b>1313</b>
	140	33	62	22.8	4300	5000	2.5	<b>1313K</b>
	140	48	95	32.5	4000	4800	3.4	<b>2313</b>