



Principal Dimension					Basic Load Rating		Fatigue	Speed Rating		Mass	Designation
d	D	T	B	C	Dynamic	Static	Load Limit	Reference Speed	Limiting Speed	kg	
mm					C	Co	Pu	Grease	Oil		
					kN		kN	RPM			
<b>65</b>	100	23	23	17,5	96,5	127	14	5000	6000	0,63	<b>32013X</b>
	100	27	27	21	110	153	17,3	5000	6300	0,78	<b>33013</b>
	110	28	28	22,5	143	283	21,2	4800	6300	1,05	<b>JM 511946/910</b>
	110	31	31	25	138	193	22,4	4300	6300	1,15	<b>T2DD 065</b>
	110	34	34	26,5	142	208	24	4300	5600	1,30	<b>33113</b>
	120	24,75	23	20	132	134	16,3	4500	5600	1,15	<b>30213</b>
	120	32,75	31	27	151	193	22,8	4000	5600	1,50	<b>32213</b>
	120	41	41	32	194	270	30,5	3800	5300	2,05	<b>33213</b>
	130	37	33,5	26	180	216	25,5	3800	5000	2,20	<b>T7FC 065</b>
	140	36	33	28	194	228	27,5	3600	4800	2,40	<b>30313</b>
140	36	33	23	190	193	23,6	3600	4800	2,35	<b>31313</b>	
140	51	48	39	264	335	40	3400	4800	3,45	<b>32313</b>	
<b>70</b>	110	25	25	19	116	153	17,3	4500	5600	0,84	<b>32014 X</b>
	110	31	31	25,5	130	196	22,8	4300	5600	1,10	<b>33014</b>
	120	37	37	29	172	250	30	4000	5300	1,70	<b>33114</b>
	125	26,25	24	21	125	156	18	4000	5300	1,25	<b>30214</b>
	125	33,25	31	27	157	208	24,5	3800	5300	1,60	<b>32214</b>
	125	41	41	32	201	285	32,5	3600	5000	2,10	<b>33214</b>
	130	43	42	35	233	325	38	3800	5600	2,45	<b>T2ED 070</b>
	140	39	35,5	27	204	240	27,5	3400	4500	2,65	<b>T7FC 070</b>
	150	38	35	30	220	260	34	3400	4500	2,90	<b>30314</b>
	150	38	35	25	216	220	27	3400	4500	2,95	<b>31314</b>
150	54	51	42	297	380	45	3200	4500	4,30	<b>32314</b>	
<b>75</b>	105	20	20	16	81,5	116	13,2	4800	6300	0,52	<b>32915</b>
	115	25	25	19	122	163	18,6	4300	5300	0,90	<b>32015</b>
	115	31	31	25,5	134	228	26	4000	5300	1,15	<b>33015</b>
	120	31	29,5	25	160	216	25	4300	5600	1,30	<b>JM714249/210</b>
	125	37	37	29	176	265	31,5	3800	5000	1,80	<b>33115</b>
	130	27,25	25	22	140	176	20,4	3800	5000	1,40	<b>30215</b>
	130	33,25	31	27	161	212	24,5	3600	5000	1,70	<b>32215</b>
	130	41	41	31	209	300	34	3400	4800	2,25	<b>33215</b>
	150	42	38	29	232	280	31	3200	4300	3,25	<b>T7FC 075</b>
	160	40	37	31	246	290	34	3200	4300	3,45	<b>30315</b>
160	40	37	26	240	245	29	3200	4300	3,50	<b>31315</b>	
160	58	55	45	336	440	51	3000	4300	5,20	<b>32315</b>	
<b>80</b>	125	29	29	22	138	216	24,5	3600	5000	1,30	<b>32016X</b>
	125	36	36	29,5	168	285	32	3600	5000	1,65	<b>33016</b>
	130	35	38	31,5	176	275	32,5	3600	5300	1,70	<b>JM 515649/610</b>
	130	37	37	29	179	280	32,5	3600	4800	1,90	<b>33116</b>
	140	28,25	26	22	151	183	21,2	3400	4800	1,60	<b>30216</b>
	140	35,25	33	28	187	245	28,5	3400	4500	2,05	<b>32216</b>
	140	46	46	35	251	375	41,5	3200	4500	2,90	<b>33216</b>
	160	45	41	31	260	315	35,5	3000	4000	3,95	<b>T7FC 080</b>
	170	42,5	39	33	270	320	38	3000	4300	4,10	<b>30316</b>
	170	42,5	39	27	260	265	32	3000	4000	4,05	<b>31316</b>
170	61,5	58	48	380	500	57	3000	4300	6,20	<b>32316</b>	